



FINANOX 8

DESCRIPTION : Secondary heat stabilizer for polar polymers

SPECIFICATIONS : Appearance : Flakes
Melting point : 37 - 46 deg C

(Slight variations in the specifications stated due to raw materials and production conditions are possible though they have no influence on the application properties described.)

APPLICATIONS :

- Imparts **excellent colour stability** during processing, fabrication and end-use.
- **Suitable for recycling/reprocessing of polymers such as PET**
- Performs synergistically when used in combination with primary stabilizers.
- Effective performance in outdoor applications - PP moulded furniture, HDPE moulded products

PROPERTIES :

- Reduces discoloration of polymers containing pigments and when processed at higher temperatures
- Minimizes the thermal degradation of polymers during processing

METHOD OF USE & USE LEVEL :

Polyolefins	0.01 - 0.2%
Styrenics	0.3 - 0.7%
PET	0.05 - 0.2%

STORAGE : Due to inherent physical properties it may form lumps (caking) during transit and storage, even if it is kept in packed condition. The caking has no negative effect on the performance of the product.

Disclaimer: Information given herein is in good faith but without guarantee since the conditions of use of the product are not in our control. Fine Organic Industries Ltd & it's associate companies expressly disclaims any responsibility for the suitability of the products for any specific or particular purposes by the user and does not assume any liability or risk involved in the use of its products. We recommend that the actual user make tests to determine the suitability of a product for their particular application prior to use. User should refer to SDS and other relevant data for safe handling. The user of the products is solely responsible for compliance with all laws and regulations applying to the use of the products, including intellectual property rights of third parties.